

## Rubberised magnet systems

### NdFeB magnetic system, black rubber sheath, with suction cup and internal thread



Article number	D mm	H mm	Adhesive force* N	Weight g	Temperature °C	Surface	Thread M
VS090NDD-04s-01	90	6	290	40	80	black	M4
VS125NDD-06s-01	125	8,5	550	127	80	black	M6
VS180NDD-06s-01	180	8,5	1,000	274	80	black	M6

#### PRODUCT INFORMATION:

Our **vakuLine magnetic systems** are ideal for use on sensitive surfaces. The special **rubber coating** prevents scratches and discolouration. At the same time, the rubber coating increases the adhesive force. An additional **soft suction cup** also creates a vacuum, which provides extra security - even with jerky movements. This vakuLine variant has an integrated **internal thread**.

As an alternative to the standard version, we also offer customised solutions:

- " Other colours for the rubber coating
- " Harder or softer rubber coating

<sup>1</sup> Due to production reasons a cylinder bore is on the holding

\* The forces have been determined at room temperature on a polished plate made of steel (S235JR according to DIN 10 025) with a thickness of 10 mm (1kg~10N). A deviation of up to -10% from the specified value is possible in exceptional cases. In general, the value is exceeded. The type of application (installation situation, temperatures, counter anchors, etc.) sometimes influence the forces enormously. The values given are for orientation purposes. Let our experts advise you.